



SIMIRON 860JF is a high performance, semi-rigid polyurea used for filling control and construction joints in concrete floors. Unlike many competitive products, this 100% Solids, VOC Free system features a fast-setting formula, provides excellent UV resistance, is moisture insensitive and offers a large shave-time window.

860JF supports and protects joint edges from heavy loads and wheel traffic, reducing spalling of the joint edges.

CUSTOM COLORS AVAILABLE

For additional custom color matching or information contact a SIMIRON representative for more help at SIMIRON.com
866-515-8775 | info@simiron.com



made in THE USA

30000199 10/17

860JF

POLYUREA JOINT FILLER

JOINT FILL COVERAGE CHART

Joint Fill Linear Feet Per Gallon							
INCHES	1/8	3/16	1/4	3/8	1/2	3/4	1
1/4	318	283	249	193	138	92	64
1/2	295	207	138	103	69	45	34
3/4	197	138	92	70	45	30	23
1	138	104	64	50	34	23	17
1 1/4	112	76	54	41	28	19	14
1 1/2	99	69	45	34	23	15	11
1 3/4	84	59	39	29	19	13	9
2	70	52	32	25	17	11	8
2 1/2	55	41	26	19	13	9	6

Joint Fill Linear Feet Per 600ml Cartridge Set							
INCHES	1/8	3/16	1/4	3/8	1/2	3/4	1
1/4	58	44	32	28	24	16	11
1/2	48	32	24	17	11	8	6
3/4	32	21	16	12	8	5	3
1	24	14	11	8	6	3	2
1 1/4	18	12	9	7	5	2	1
1 1/2	16	10	8	6	4	2	1
1 3/4	13	9	7	5	3	2	1
2	12	7	5	3	2	1	0.9
2 1/2	10	5	3	2	1	0.9	0.4

Recommended average coverage rates for 860JF based on typical coverage rates that can be expected in the field.
**Recommended Joint Fill Coverage contain a 10% deduction pre-calculated for waste and overfill.



32700 Industrial Drive,
Madison Heights, MI 48071
866.515.8775 SIMIRON.COM