

**Safety Data Sheet (SDS)**

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 10/02/2015

Reviewed on 10/02/2015

**1 Identification**

- **Product Identifier**
- **Trade name: 650WB Activator**
- **Relevant identified uses of the substance or mixture and uses advised against:**
- **Product Description** Waterbased Epoxy Floor Coating
- **Details of the Supplier of the Safety Data Sheet:**
- **Manufacturer/Supplier:**  
SIMIRON  
32700 Industrial Drive  
Madison Heights, MI 48071  
Phone: (248) 686-3600  
Fax: (248) 677-9325  
www.simiron.com
- **Emergency telephone number:** 800-535-5053

**2 Hazard(s) Identification**

- **Classification of the substance or mixture:**



GHS09 Environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.  
Eye Irrit. 2A H319 Causes serious eye irritation.  
Skin Sens. 1 H317 May cause an allergic skin reaction.

- **Label elements:**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms:**



GHS07 GHS09

- **Signal word:** Warning
- **Hazard-determining components of labeling:**  
Epoxy resin  
oxirane, mono[(C12-14-alkyloxy)methyl] derivs
- **Hazard statements:**  
Causes skin irritation.  
Causes serious eye irritation.  
May cause an allergic skin reaction.  
Toxic to aquatic life with long lasting effects.
- **Precautionary statements:**  
Avoid breathing dust/fume/gas/mist/vapors/spray.  
Wear protective gloves.

## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 10/02/2015

Reviewed on 10/02/2015

### Trade name: 650WB Activator

- Wear eye protection / face protection.
- Avoid release to the environment.
- Wash thoroughly after handling.
- Contaminated work clothing must not be allowed out of the workplace.
- If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- Specific treatment (see supplementary first aid instructions on this Safety Data Sheet).
- Wash contaminated clothing before reuse.
- If skin irritation occurs: Get medical advice/attention.
- If skin irritation or rash occurs: Get medical advice/attention.
- If eye irritation persists: Get medical advice/attention.
- IF ON SKIN: Wash with plenty of water.
- Collect spillage.
- Take off contaminated clothing and wash it before reuse.
- Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



· **HMS-ratings (scale 0 - 4)**

HEALTH	1	Health = 1
FIRE	1	Fire = 1
REACTIVITY	0	Reactivity = 0

· **Hazard(s) not otherwise classified (HNOC):** None known

### 3 Composition/Information on Ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture: consisting of the following components.

· **Dangerous Components:**

25068-38-6	Epoxy resin	85-95%
	⚠ Aquatic Chronic 2, H411; ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	
68609-97-2	oxirane, mono[(C12-14-alkyloxy)methyl] derivs	5-10%
	⚠ Skin Irrit. 2, H315; Skin Sens. 1, H317	

### 4 First-Aid Measures

- **Description of first aid measures:**
- **After inhalation:**  
Supply fresh air; consult doctor in case of complaints.  
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:**  
Immediately wash skin with soap and plenty of water for at least 15 minutes.  
Remove contaminated clothing and wash before reuse.  
Get medical attention if symptoms occur.
- **After eye contact:**  
Rinse opened eye for at least 15 minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If swallowed and symptoms occur, consult a doctor.

(Contd. on page 3)

## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 10/02/2015

Reviewed on 10/02/2015

**Trade name: 650WB Activator**

- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed:** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed:**  
No further relevant information available.

### 5 Fire-Fighting Measures

- **Extinguishing media:**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture:** Phenolics. Carbon monoxide. Carbon dioxide.
- **Advice for firefighters:**
- **Protective equipment:**  
As in any fire, wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear to prevent contact with skin and eyes.

### 6 Accidental Release Measures

- **Personal precautions, protective equipment and emergency procedures:**  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**  
Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**  
Ensure adequate ventilation.  
Absorb with liquid-binding material (i.e. sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to section 13.
- **Reference to other sections:**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

### 7 Handling and Storage

- **Handling**
- **Precautions for safe handling:**  
Ensure good ventilation/exhaustion at the workplace.  
Prevent formation of aerosols.  
Avoid contact with skin, eyes and clothing
- **Information about protection against explosions and fires:** No special measures required.
- **Conditions for safe storage, including any incompatibilities:**
- **Storage**
- **Requirements to be met by storerooms and receptacles:** Store in a cool, dry place.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** No further relevant information available..
- **Specific end use(s):** No further relevant information available.

### 8 Exposure Controls/Personal Protection

- **Additional information about design of technical systems:** No further data; see section 7.

(Contd. on page 4)

## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 10/02/2015

Reviewed on 10/02/2015

**Trade name: 650WB Activator**

· **Control parameters:**

· **Components with occupational exposure limits:**

**25068-38-6 Epoxy resin**

PEL	Short-term value: 5 mg/m <sup>3</sup> Long-term value: 15 mg/m <sup>3</sup>
STEL	Short-term value: 5 mg/m <sup>3</sup> Long-term value: 10 mg/m <sup>3</sup>

· **Additional information:** The lists that were valid during the creation of this SDS were used as basis.

· **Exposure controls:**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing and wash before reuse.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· **Breathing equipment:**



NIOSH/OSHA or EN approved respiratory protection is recommended for use in airborne concentrations exceeding exposure limits.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Select glove material based on penetration times, rates of diffusion and degradation.

· **Material of gloves:**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material cannot be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material:**

The exact break-through time has to be determined and observed by the manufacturer of the protective gloves.

· **Eye protection:**



Tightly sealed goggles

(Contd. on page 5)

## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 10/02/2015

Reviewed on 10/02/2015

**Trade name: 650WB Activator**

### 9 Physical and Chemical Properties

- **Information on basic physical and chemical properties**
- **General Information**
- **Appearance:**
  - Form:** Liquid
  - Color:** Clear
- **Odor:** Not determined
- **Odor threshold:** Not determined.
- **Change in condition**
  - Melting point/Melting range:** Not determined.
  - Boiling point/Boiling range:** 218 °C (424 °F)
- **Flash point:** 150 °C (302 °F)
- **Flammability (solid, gaseous):** Not applicable.
- **Ignition temperature:** Not determined
- **Decomposition temperature:** Not determined.
- **Auto igniting:** Product is not self-igniting.
- **Danger of explosion:** Product does not present an explosion hazard.
- **Explosion limits:**
  - Lower:** Not determined.
  - Upper:** Not determined.
- **Vapor pressure:** Not determined.
- **Density @ 20 °C (68 °F):** 1.14 g/cm<sup>3</sup> (9.513 lbs/gal)
- **Relative density:** Not determined.
- **Vapor density:** Not determined.
- **Evaporation rate:** Not determined.
- **Solubility in / Miscibility with:**
  - Water:** Not miscible or difficult to mix.
- **Partition coefficient (n-octanol/water):** Not determined.
- **Viscosity:**
  - Dynamic:** Not determined.
  - Kinematic:** Not determined.
- **Solvent content:**
  - Organic solvents:** 0.0 %
  - Solids content:** 90.0 %
- **Other information:** No further relevant information available.

### 10 Stability and Reactivity

- **Reactivity:** No further relevant information available.
- **Chemical stability:** Stable under normal conditions.
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions:** No dangerous reactions known.
- **Conditions to avoid:** No further relevant information available.
- **Incompatible materials:** Strong oxidizers; Strong acids; Strong bases; Amines

(Contd. on page 6)

## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 10/02/2015

Reviewed on 10/02/2015

**Trade name: 650WB Activator**

- **Hazardous decomposition products:** Phenolics, carbon monoxide

### 11 Toxicological Information

- **Information on toxicological effects:**
- **Acute toxicity:**

· <b>LD/LC50 values that are relevant for classification:</b>		
<b>25068-38-6 Epoxy resin</b>		
Oral	LD50	>2000 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rat)
<b>68609-97-2 oxirane, mono[(C12-14-alkyloxy)methyl] derivs</b>		
Oral	LD50	19200 mg/kg (rat)
Dermal	LD50	4500 mg/kg (rabbit)

- **Primary irritant effect:**
- **On the skin:**  
Irritant to skin and mucous membranes.  
May cause an allergic skin reaction.
- **On the eye:** Irritating effect.
- **Sensitization:** Sensitization possible through skin contact.
- **Additional toxicological information:**  
The product shows the following dangers according to internally approved calculation methods for preparations:  
Irritant

- **Carcinogenic categories:**

· <b>IARC (International Agency for Research on Cancer):</b>
None of the ingredients are listed.
· <b>NTP (National Toxicology Program):</b>
None of the ingredients are listed.
· <b>OSHA-Ca (Occupational Safety &amp; Health Administration):</b>
None of the ingredients are listed.

### 12 Ecological Information

- **Toxicity:**
- **Aquatic toxicity:**  
Avoid release into the environment. Runoff from fire control or dilution water may cause pollution.

<b>25068-38-6 Epoxy resin</b>	
EC50	3.6 mg/l (daphnia)

- **Persistence and degradability:** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential:** No further relevant information available.
- **Mobility in soil:** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Toxic for fish
- **Additional ecological information:**
- **General notes:**  
Do not allow product to reach ground water, water course or sewage system.  
Danger to drinking water if even small quantities leak into the ground.  
Poisonous for fish and plankton in water bodies.

## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 10/02/2015

Reviewed on 10/02/2015

**Trade name: 650WB Activator**



- Toxic for aquatic organisms
- **Results of PBT and vPvB assessment:**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects:** No further relevant information available.

### 13 Disposal Considerations

- **Waste treatment methods:**
- **Recommendation:**  
Must not be disposed of together with household garbage. Do not allow product to reach sewage system. Observe all federal, state and local environmental regulations when disposing of this material.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

### 14 Transport Information

- **UN-Number:**
- **DOT, ADR, IATA** Non-Regulated Material
- **IMDG** UN3082
- **UN proper shipping name:**
- **DOT, ADR, IATA** Non-Regulated Material
- **IMDG** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy resin), MARINE POLLUTANT
- **Transport hazard class(es):**
- **DOT, ADR, IATA**
- **Class:** Non-Regulated Material

- **IMDG**
-  
- **Class:** 9 Miscellaneous dangerous substances and articles
- **Label:** 9
- **Packing group:**
- **DOT, ADR, IATA** Non-Regulated Material
- **IMDG** III
- **Environmental hazards:** Product contains environmentally hazardous substances: Epoxy resin
- **Special precautions for user:** Not applicable.
- **EMS Number:** F-A,S-F
- **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code:** Not applicable.
- **Transport/Additional information:**

- **IMDG**
- **Limited quantities (LQ):** 5L
- **Excepted quantities (EQ):** Code: E1  
Maximum net quantity per inner packaging: 30 ml  
Maximum net quantity per outer packaging: 1000 ml

(Contd. on page 8)

## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 10/02/2015

Reviewed on 10/02/2015

**Trade name: 650WB Activator**

· **UN "Model Regulation":** Non-Regulated Material

### 15 Regulatory Information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture:**  
 · **SARA (Superfund Amendments and Reauthorization):**

· **Section 355 (extremely hazardous substances):**

None of the ingredients are listed.

· **Section 313 (Specific toxic chemical listings):**

None of the ingredients are listed.

· **TSCA (Toxic Substances Control Act):**

All ingredients are listed.

· **California Proposition 65:**

· **Chemicals known to cause cancer:**

None of the ingredients are listed.

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients are listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients are listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients are listed.

· **Carcinogenic categories:**

· **EPA (Environmental Protection Agency):**

None of the ingredients are listed.

· **TLV (Threshold Limit Value established by ACGIH):**

None of the ingredients are listed.

· **NIOSH-Ca (National Institute for Occupational Safety and Health):**

None of the ingredients are listed.

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms:**



GHS07 GHS09

· **Signal word:** Warning

· **Hazard-determining components of labeling:**

Epoxy resin  
 oxirane, mono[(C12-14-alkyloxy)methyl] derivs

· **Hazard statements:**

Causes skin irritation.  
 Causes serious eye irritation.  
 May cause an allergic skin reaction.  
 Toxic to aquatic life with long lasting effects.



## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 10/02/2015

Reviewed on 10/02/2015

**Trade name: 650WB Activator**

**Precautionary statements:**

- Avoid breathing dust/fume/gas/mist/vapors/spray.
- Wear protective gloves.
- Wear eye protection / face protection.
- Avoid release to the environment.
- Wash thoroughly after handling.
- Contaminated work clothing must not be allowed out of the workplace.
- If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- Specific treatment (see supplementary first aid instructions on this Safety Data Sheet).
- Wash contaminated clothing before reuse.
- If skin irritation occurs: Get medical advice/attention.
- If skin irritation or rash occurs: Get medical advice/attention.
- If eye irritation persists: Get medical advice/attention.
- IF ON SKIN: Wash with plenty of water.
- Collect spillage.
- Take off contaminated clothing and wash it before reuse.
- Dispose of contents/container in accordance with local/regional/national/international regulations.

**National regulations:**

The product is subject to be classified according with the latest version of the regulations on hazardous substances.

**State Right to Know:**

25068-38-6	Epoxy resin ⚠ Aquatic Chronic 2, H411; ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	85-95%
68609-97-2	oxirane, mono[(C12-14-alkyloxy)methyl] derivs ⚠ Skin Irrit. 2, H315; Skin Sens. 1, H317	5-10%

All ingredients are listed.

**Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### 16 Other Information

The information and recommendations in this safety data sheet are, to the best of our knowledge, accurate as of the date of issue. Nothing herein shall be deemed to create warranty, expressed or implied, and shall not establish a legally valid contractual relationship. It is the responsibility of the user to determine applicability of this information and the suitability of the material or product for any particular purpose.

**Date of preparation / last revision:** 10/02/2015 / -

**Abbreviations and acronyms:**

- ADR: The European Agreement concerning the International Carriage of Dangerous Goods by Road
- ADN: The European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
- IMDG: International Maritime Code for Dangerous Goods
- DOT: US Department of Transportation
- IATA: International Air Transport Association
- ACGIH: American Conference of Governmental Industrial Hygienists
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- NFPA: National Fire Protection Association (USA)
- HMS: Hazardous Materials Identification System (USA)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2
- Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2
- Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A
- Skin Sens. 1: Sensitisation - Skin, Hazard Category 1



## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 10/02/2015

Reviewed on 10/02/2015

**Trade name: 650WB Activator**

Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2

· \* **Data compared to the previous version altered.**

SDS created by MSDS Authoring Services [www.msdsauthoring.com](http://www.msdsauthoring.com) +1-877-204-9106