



## SAFETY DATA SHEET (SDS)

OSHA Hazard Communication Standard 29 CFR 1910.1200. Prepared to GHS Rev03.

**Product name:** 6,0,52167,15(6,1

**Issue Date:** 09/20/19

---

### 1. IDENTIFICATION

---

**Product name:** SIMIRON CASTING RESIN CLEAR

**Item #'s:**

#### COMPANY IDENTIFICATION

SIMIRON, INC.  
32700 INDUSTRIAL DRIVE  
MADISON HEIGHTS, MI 48071  
UNITED STATES

**Customer Information Number:** TOLL FREE: 866-515-8775

**PHONE 248-686-3600**

**INFO@SIMIRON.COM**

**WWW.SIMIRON.COM**

#### EMERGENCY TELEPHONE NUMBER

**24-Hour Emergency Contact:** 1 800 535-5053

**Local Emergency Contact:** 1 352-326-2510

---

### 2. HAZARDS IDENTIFICATION

---

#### Hazard classification

This material is hazardous under the criteria of the Federal OSHA Hazard Communication Standard 29CFR 1910.1200.

Skin irritation - Category 2

Eye irritation - Category 2B

Skin sensitisation - Sub-category 1B

#### Label elements

**Hazard pictograms**



GHS07

Signal word: **WARNING!****Hazards**

Skin Irrit. 2 H315 Causes skin irritation.  
 Eye Irrit. 2A H319 Causes serious eye irritation.  
 Skin Sens. 1 H317 May cause an allergic skin reaction.

**Precautionary statements****Prevention**

Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.  
 Wash skin thoroughly after handling.  
 Contaminated work clothing should not be allowed out of the workplace.  
 Wear protective gloves.

**Response**

IF ON SKIN: Wash with plenty of soap and water.  
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 If skin irritation or rash occurs: Get medical advice/ attention.  
 If eye irritation persists: Get medical advice/ attention.  
 Take off contaminated clothing and wash before reuse.

**Disposal**

Dispose of contents/ container to an approved waste disposal plant.

**Other hazards**

No data available

---



---

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

---

**Synonyms:** Liquid Epoxy Resin

This product is a substance.

Component	CASRN	Concentration
Propane, 2,2-bis[p-(2,3-epoxypropoxy)phenyl]-, polymers	25085-99-8	100.0%

*Note*

---

## 4. FIRST AID MEASURES

---

### Description of first aid measures

**General advice:** First Aid responders should pay attention to self-protection and use the recommended protective clothing (chemical resistant gloves, splash protection). If potential for exposure exists refer to Section 8 for specific personal protective equipment.

**Inhalation:** Move person to fresh air; if effects occur, consult a physician.

**Skin contact:** Remove material from skin immediately by washing with soap and plenty of water. Remove contaminated clothing and shoes while washing. Seek medical attention if irritation persists. Wash clothing before reuse. Discard items which cannot be decontaminated, including leather articles such as shoes, belts and watchbands.

**Eye contact:** Flush eyes thoroughly with water for several minutes. Remove contact lenses after the initial 1-2 minutes and continue flushing for several additional minutes. If effects occur, consult a physician, preferably an ophthalmologist. Suitable emergency eye wash facility should be available in work area.

**Ingestion:** No emergency medical treatment necessary.

**Most important symptoms and effects, both acute and delayed:** Aside from the information found under Description of first aid measures (above) and Indication of immediate medical attention and special treatment needed (below), any additional important symptoms and effects are described in Section 11: Toxicology Information.

### Indication of any immediate medical attention and special treatment needed

**Notes to physician:** No specific antidote. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

---

## 5. FIREFIGHTING MEASURES

---

**Suitable extinguishing media:** Water fog or fine spray. Dry chemical fire extinguishers. Carbon dioxide fire extinguishers. Foam. Alcohol resistant foams (ATC type) are preferred. General purpose synthetic foams (including AFFF) or protein foams may function, but will be less effective. Water fog, applied gently may be used as a blanket for fire extinguishment.

**Unsuitable extinguishing media:** Do not use direct water stream. May spread fire.

### Special hazards arising from the substance or mixture

**Hazardous combustion products:** During a fire, smoke may contain the original material in addition to combustion products of varying composition which may be toxic and/or irritating. Combustion products may include and are not limited to: Phenolics. Carbon monoxide. Carbon dioxide.

**Unusual Fire and Explosion Hazards:** Container may rupture from gas generation in a fire situation. Violent steam generation or eruption may occur upon application of direct water stream to hot liquids. Dense smoke is emitted when burned without sufficient oxygen.

### Advice for firefighters

**Fire Fighting Procedures:** Keep people away. Isolate fire and deny unnecessary entry. Use water spray to cool fire exposed containers and fire affected zone until fire is out and danger of reignition has passed. Fight fire from protected location or safe distance. Consider the use of unmanned hose

holders or monitor nozzles. Immediately withdraw all personnel from the area in case of rising sound from venting safety device or discoloration of the container. Do not use direct water stream. May spread fire. Move container from fire area if this is possible without hazard. Burning liquids may be moved by flushing with water to protect personnel and minimize property damage. Water fog, applied gently may be used as a blanket for fire extinguishment. Contain fire water run-off if possible. Fire water run-off, if not contained, may cause environmental damage. Review the "Accidental Release Measures" and the "Ecological Information" sections of this (M)SDS.

**Special protective equipment for firefighters:** Wear positive-pressure self-contained breathing apparatus (SCBA) and protective fire fighting clothing (includes fire fighting helmet, coat, trousers, boots, and gloves). Avoid contact with this material during fire fighting operations. If contact is likely, change to full chemical resistant fire fighting clothing with self-contained breathing apparatus. If this is not available, wear full chemical resistant clothing with self-contained breathing apparatus and fight fire from a remote location. For protective equipment in post-fire or non-fire clean-up situations, refer to the relevant sections.

---

## **6. ACCIDENTAL RELEASE MEASURES**

---

**Personal precautions, protective equipment and emergency procedures:**

**Environmental precautions:** Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information.

**Methods and materials for containment and cleaning up:** Contain spilled material if possible. Absorb with materials such as: Sand. Polypropylene fiber products. Polyethylene fiber products. Remove residual with soap and hot water. Collect in suitable and properly labeled containers. Residual can be removed with solvent. Solvents are not recommended for clean-up unless the recommended exposure guidelines and safe handling practices for the specific solvent are followed. Consult appropriate solvent Safety Data Sheet for handling information and exposure guidelines. See Section 13, Disposal Considerations, for additional information.

---

## **7. HANDLING AND STORAGE**

---

**Precautions for safe handling:** Avoid prolonged or repeated contact with skin. Avoid contact with eyes, skin, and clothing. Wash thoroughly after handling. Spills of these organic materials on hot fibrous insulations may lead to lowering of the autoignition temperatures possibly resulting in spontaneous combustion. See Section 8, EXPOSURE CONTROLS AND PERSONAL PROTECTION.

**Conditions for safe storage:** Recommended storage temperature is 55°F (13°C) - 95°F (35°C). Additional storage and handling information on this product may be obtained by calling your sales or customer service contact. Ask for a product brochure.

**Storage stability**

<b>Storage temperature:</b>	<b>Shelf life: Use within</b>
55 - 95 °F (13 - 35 °C)	18 Month

---

## **8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

---

**Control parameters**

Exposure limits are listed below, if they exist.

Exposure limits have not been established for those substances listed in the composition, if any have been disclosed.

### Exposure controls

**Engineering controls:** Use local exhaust ventilation, or other engineering controls to maintain airborne levels below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, general ventilation should be sufficient for most operations. Local exhaust ventilation may be necessary for some operations.

### Individual protection measures

**Eye/face protection:** Use safety glasses (with side shields).

#### Skin protection

**Hand protection:** Use gloves chemically resistant to this material. Examples of preferred glove barrier materials include: Butyl rubber. Ethyl vinyl alcohol laminate ("EVAL"). Nitrile/butadiene rubber ("nitrile" or "NBR"). Neoprene. Polyvinyl chloride ("PVC" or "vinyl"). NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.

**Other protection:** Use protective clothing chemically resistant to this material. Selection of specific items such as face shield, boots, apron, or full body suit will depend on the task.

**Respiratory protection:** Respiratory protection should be worn when there is a potential to exceed the exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, wear respiratory protection when adverse effects, such as respiratory irritation or discomfort have been experienced, or where indicated by your risk assessment process. For most conditions, no respiratory protection should be needed; however, if material is heated or sprayed, use an approved air-purifying respirator. The following should be effective types of air-purifying respirators: Organic vapor cartridge with a particulate pre-filter.

---

## 9. PHYSICAL AND CHEMICAL PROPERTIES

---

### Appearance

<b>Physical state</b>	viscous Liquid.
<b>Color</b>	Colorless/Clear/Slight Haze
<b>Odor</b>	Odorless to mild
<b>Odor Threshold</b>	No test data available
<b>pH</b>	No test data available
<b>Melting point/range</b>	Not applicable
<b>Freezing point</b>	No test data available
<b>Boiling point (760 mmHg)</b>	320 °C ( 608 °F) <i>Differential Scanning Calorimetry (DSC)</i> Decomposition
<b>Flash point</b>	<b>closed cup</b> 264 - 268 °C ( 507 - 514 °F) at 102.89 hPa <i>EC Method A9</i>
<b>Evaporation Rate (Butyl Acetate = 1)</b>	No test data available

<b>Flammability (solid, gas)</b>	No
<b>Lower explosion limit</b>	Not applicable
<b>Upper explosion limit</b>	Not applicable
<b>Vapor Pressure</b>	< 0.0000001 Pa <i>EC Method A4</i>
<b>Relative Vapor Density (air = 1)</b>	No data available
<b>Relative Density (water = 1)</b>	1.16 at 20 °C (68 °F) / 20 °C <i>Literature</i>
<b>Water solubility</b>	5.4 - 8.4 mg/l at 20 °C (68 °F) <i>EU Method A.6 (Water Solubility)</i>
<b>Partition coefficient: n-octanol/water</b>	log Pow: 3.242 <i>Estimated.</i>
<b>Auto-ignition temperature</b>	Not applicable
<b>Decomposition temperature</b>	No test data available
<b>Dynamic Viscosity</b>	11,000 - 14,000 mPa.s at 25 °C (77 °F) <i>ASTM D 445</i>
<b>Kinematic Viscosity</b>	No test data available
<b>Explosive properties</b>	No <i>EEC A14</i>
<b>Oxidizing properties</b>	No
<b>Liquid Density</b>	1.16 g/cm <sup>3</sup> at 25 °C (77 °F) <i>ASTM D4052</i>
<b>Molecular weight</b>	Not determined
<b>Particle size</b>	Not determined

NOTE: The physical data presented above are typical values and should not be construed as a specification.

---

## 10. STABILITY AND REACTIVITY

---

**Reactivity:** No data available

**Chemical stability:** Stable under recommended storage conditions. See Storage, Section 7.

**Possibility of hazardous reactions:** Will not occur by itself. Masses of more than one pound (0.5 kg) of product plus an aliphatic amine will cause irreversible polymerization with considerable heat build-up.

**Conditions to avoid:** Avoid short term exposures to temperatures above 300 °C  
Potentially violent decomposition can occur above 350 °C  
Avoid prolonged exposure to temperatures above 250 °C  
Generation of gas during decomposition can cause pressure in closed systems. Pressure build-up can be rapid.

**Incompatible materials:** Avoid contact with oxidizing materials. Avoid contact with: Acids. Bases. Avoid unintended contact with amines.

**Hazardous decomposition products:** Decomposition products depend upon temperature, air supply and the presence of other materials. Gases are released during decomposition. Uncontrolled exothermic reaction of epoxy resins release phenolics, carbon monoxide, and water.

---

---

## 11. TOXICOLOGICAL INFORMATION

---

*Toxicological information appears in this section when such data is available.*

### **Acute toxicity**

#### **Acute oral toxicity**

Very low toxicity if swallowed. Harmful effects not anticipated from swallowing small amounts.

LD50, Rat, > 15,000 mg/kg

#### **Acute dermal toxicity**

Prolonged skin contact is unlikely to result in absorption of harmful amounts.

LD50, Rabbit, 23,000 mg/kg

#### **Acute inhalation toxicity**

At room temperature, exposure to vapor is minimal due to low volatility. Vapor from heated material, mist or aerosols may cause respiratory irritation.

The LC50 has not been determined.

### **Skin corrosion/irritation**

Prolonged contact may cause skin irritation with local redness.

Repeated contact may cause skin irritation with local redness.

### **Serious eye damage/eye irritation**

May cause eye irritation.

Corneal injury is unlikely.

### **Sensitization**

For similar material(s):

Has caused allergic skin reactions in humans.

Has demonstrated the potential for contact allergy in mice.

For respiratory sensitization:

No relevant data found.

### **Specific Target Organ Systemic Toxicity (Single Exposure)**

Evaluation of available data suggests that this material is not an STOT-SE toxicant.

### **Specific Target Organ Systemic Toxicity (Repeated Exposure)**

Except for skin sensitization, repeated exposures to low molecular weight epoxy resins of this type are not anticipated to cause any significant adverse effects.

### **Carcinogenicity**

Many studies have been conducted to assess the potential carcinogenicity of diglycidyl ether of bisphenol A (DGEBA). Indeed, the most recent review of the available data by the International Agency for Research on Cancer (IARC) has concluded that DGEBA is not classified as a carcinogen. Although some weak evidence of carcinogenicity has been reported in animals, when all of the data are considered, the weight of evidence does not show that DGEBA is carcinogenic.

**Teratogenicity**

Resins based on the diglycidyl ether of bisphenol A (DGEBA) did not cause birth defects or other adverse effects on the fetus when pregnant rabbits were exposed by skin contact, the most likely route of exposure, or when pregnant rats or rabbits were exposed orally.

**Reproductive toxicity**

In animal studies, did not interfere with reproduction.

**Mutagenicity**

In vitro genetic toxicity studies were negative in some cases and positive in other cases. Animal genetic toxicity studies were negative.

**Aspiration Hazard**

Based on physical properties, not likely to be an aspiration hazard.

**COMPONENTS INFLUENCING TOXICOLOGY:**

**Propane, 2,2-bis[p-(2,3-epoxypropoxy)phenyl]-, polymers**

**Acute inhalation toxicity**

The LC50 has not been determined.

---

**12. ECOLOGICAL INFORMATION**

---

*Ecotoxicological information appears in this section when such data is available.*

**Toxicity**

**Acute toxicity to fish**

Material is moderately toxic to aquatic organisms on an acute basis (LC50/EC50 between 1 and 10 mg/L in the most sensitive species tested).

LC50, *Oncorhynchus mykiss* (rainbow trout), semi-static test, 96 Hour, 2 mg/l

**Acute toxicity to aquatic invertebrates**

EC50, *Daphnia magna* (Water flea), static test, 48 Hour, 1.8 mg/l

**Acute toxicity to algae/aquatic plants**

ErC50, *Scenedesmus capricornutum* (fresh water algae), static test, 72 Hour, Growth rate inhibition, 11 mg/l

**Toxicity to bacteria**

IC50, Bacteria, 18 Hour, Respiration rates., > 42.6 mg/l

**Chronic aquatic toxicity**

**Chronic toxicity to aquatic invertebrates**

MATC (Maximum Acceptable Toxicant Level), *Daphnia magna* (Water flea), semi-static test, 21 d, number of offspring, 0.55 mg/l

**Persistence and degradability**

**Biodegradability:** Based on stringent OECD test guidelines, this material cannot be considered as readily biodegradable; however, these results do not necessarily mean that the material is not biodegradable under environmental conditions.

10-day Window: Not applicable



**Biodegradation:** 12 %  
**Exposure time:** 28 d  
**Method:** OECD Test Guideline 302B or Equivalent

**Theoretical Oxygen Demand:** 2.35 mg/mg Estimated.

**Photodegradation**  
**Test Type:** Half-life (indirect photolysis)  
**Sensitizer:** OH radicals  
**Atmospheric half-life:** 1.92 Hour  
**Method:** Estimated.

#### Bioaccumulative potential

**Bioaccumulation:** Bioconcentration potential is moderate (BCF between 100 and 3000 or Log Pow between 3 and 5).

**Partition coefficient: n-octanol/water(log Pow):** 3.242 at 25 °C Estimated.

#### Mobility in soil

Potential for mobility in soil is low (Koc between 500 and 2000).

Given its very low Henry's constant, volatilization from natural bodies of water or moist soil is not expected to be an important fate process.

**Partition coefficient(Koc):** 1800 - 4400 Estimated.

---

## 13. DISPOSAL CONSIDERATIONS

---

**Disposal methods:** DO NOT DUMP INTO ANY SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER. All disposal practices must be in compliance with all Federal, State/Provincial and local laws and regulations. Regulations may vary in different locations. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. AS YOUR SUPPLIER, WE HAVE NO CONTROL OVER THE MANAGEMENT PRACTICES OR PARTIES HANDLING OR USING THIS MATERIAL. THE INFORMATION PRESENTED HERE PERTAINS ONLY TO THE PRODUCT AS SHIPPED IN ITS INTENDED CONDITION AS DESCRIBED IN SDS SECTION: Composition Information. FOR UNUSED & UNCONTAMINATED PRODUCT, the preferred options include sending to a licensed, permitted: Incinerator or other thermal destruction device.

---

## 14. TRANSPORT INFORMATION

---

#### DOT

Not regulated for transport

#### Classification for SEA transport (IMO-IMDG):

<b>Proper shipping name</b>	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.(Epoxy resin)
<b>UN number</b>	UN 3082
<b>Class</b>	9
<b>Packing group</b>	III
<b>Marine pollutant</b>	Epoxy resin
<b>Transport in bulk</b>	Consult IMO regulations before transporting ocean bulk

according to Annex I or II  
of MARPOL 73/78 and the  
IBC or IGC Code

**Classification for AIR transport (IATA/ICAO):**

<b>Proper shipping name</b>	Environmentally hazardous substance, liquid, n.o.s.(Epoxy resin)
<b>UN number</b>	UN 3082
<b>Class</b>	9
<b>Packing group</b>	III

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

---

**15. REGULATORY INFORMATION**

---

**OSHA Hazard Communication Standard**

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

**Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Sections 311 and 312**

Acute Health Hazard

**Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Section 313**

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

**Pennsylvania Worker and Community Right-To-Know Act:**

To the best of our knowledge, this product does not contain chemicals at levels which require reporting under this statute.

**California Proposition 65 (Safe Drinking Water and Toxic Enforcement Act of 1986)**

This product contains no listed substances known to the State of California to cause cancer, birth defects or other reproductive harm, at levels which would require a warning under the statute.

**United States TSCA Inventory (TSCA)**

All components of this product are in compliance with the inventory listing requirements of the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

---

**16. OTHER INFORMATION**

---

**Product Literature**

Additional information on this product may be obtained by calling your sales or customer service contact. Ask for a product brochure. Additional information on this and other products may be obtained by visiting our web page.

**Hazard Rating System****NFPA**

Health	Fire	Reactivity
1	1	0

**Information Source and References**

This SDS is prepared by Product Regulatory Services and Hazard Communications Groups from information supplied by internal references within our company.

SIMIRON, INC. urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (M)SDSs, we are not and cannot be responsible for (M)SDSs obtained from any source other than ourselves. If you have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version.