



30 TEX AND 50 TEX - SLIP RESISTANT ADDITIVE

PRODUCT DESCRIPTION

TEX is a stir-in additive available in two sizes, 30 and 50, that provides a slip-resistant texture to Simiron floor coatings. A longer lasting surface is created by this product's ability to resist chemicals and detergents. 50 Tek measures 50 mesh and 30 Tek is larger at 30 mesh to cover a wide range of film thicknesses and texture needs.

50 TEX delivers a safer setting for home, commercial, and industrial settings. This additive works excellent for both interior and exterior surfaces and will not alter the color of the coating.

FEATURES & BENEFITS

- Add to latex-based, oil-based and epoxy coatings
- Add to paints, stains or sealers
- Add to Simiron coatings
- Easy to incorporate and maintain
- Spherical-shaped particles provide a smoother feel to touch
- Does not increase material viscosity
- Stays suspended in coating

RECOMMENDED USES

- Concrete and Masonry surfaces
- Areas that get wet or dusty
- Surfaces that are not flat/inclined
- Steps
- Garages
- Workshops

PRODUCT INFORMATION

PRODUCT NAME	SIZE	COLOR/FINISH	ITEM NUMBER
50-TEX	3.2 oz.	Clear / Gloss	40002909
30-TEX	14.8 oz.	Clear / Gloss	40002428

COVERAGE

Add one container of 50 TEX to one gallon of coating (mixed if there are multiple components). Add one container of 30 TEX to three gallons of product. The texture additive will not change the coverage rate of the coating being applied. See individual product data sheet for recommended coverage rate.

Due to the difference in substrates, environments, and preparation methods, products, and application thicknesses; always test the product in a small corner area before full application to ensure compatibility and determine texture.



30 TEX AND 50 TEX - SLIP RESISTANT ADDITIVE

LIMITATIONS

SIMIRON 50 TEX increases the coefficient of friction on the surface of a paint making the final coating slip-resistant, but due to its small particle size, it will not be skid-resistant. Do not use on wood stains.

INSTRUCTIONS

Add contents of one **50-TEX** container into one gallon of a Simiron coating* while mixing. **Simiron 50-TEX** should be mixed into the final topcoat. Mix well and apply with a roller. Occasionally stir product to keep material evenly suspended.

**Refer specific coating label and product data page for detailed product guidelines*

CAUTION

⚠ Only apply when there is adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air or wear respiratory protection (NIOSH approved) or leave the area. **FIRST AID:** In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room or physician immediately. **DO NOT TAKE INTERNALLY. KEEP OUT OF REACH OF CHILDREN.**

TECHNICAL ASSISTANCE



Information is available by calling **SIMIRON**
Toll Free: **1.866.515.8775 / +1.248.686.3600**

LIMITED WARRANTY

SIMIRON warrants this product to be free from defect in the material that affects its performance for a period of one year (from date of purchase). **SIMIRON** will replace at no charge the quantity of the Coating that **SIMIRON** determines has failed to perform, as the sole and exclusive remedy for any breach of this warranty and/or any other defect or failure of the coating. Proof of purchase is required. Cost of labor for application of any product specifically is excluded. Warranty is void if Simiron products are mixed with or used in conjunction with materials that are substituted for Simiron products. Warranty is nontransferable.



CORPORATE OFFICE:

Simiron Inc
3000 Research Drive
Rochester Hills, MI 48309-3580
USA
(248) 686-3600 / (866) 515-8775

PRODUCT DATA SHEET: 12/13/2023

Disclaimer: All information provided by Simiron, Inc. concerning Simiron products, including but not limited to, any recommendations and advice relating to the application and use of Simiron products, is given in good faith based on Simiron's current experience and knowledge of its products when properly stored, handled, and applied under normal conditions in accordance with Simiron's instructions. In practice, the differences in materials, substrates, storage and handling conditions, actual conditions and other factors outside of Simiron's control are such that Simiron assumes no liability for the provision of such information, advice, recommendations or instructions related to its products. The uses of Simiron product(s) for suitability for the intended application and purpose before proceeding with the full application of the product(s).

Simiron reserves the right to change the properties of its products without notice. All Simiron product(s) are subject to its current terms and conditions of sale which are available by calling (866) 515-8775.